



**Oracle**

**1Z0-880**

*Oracle Solaris 10 Network Administrator(R) Certified Expert*

DHCP client's dhcpagent to request additional networking information from the DHCP server. Which variable must be modified?

- A. PARAM\_REQUEST\_LIST
- B. PARAM\_REQUEST\_ADDRESS
- C. PARAM\_REQUEST\_NETWORKING
- D. PARAM\_REQUEST\_ROWS
- E. PARAM\_REQUEST

**Answer:** A

**QUESTION:** 308

Which information is found in TCP segment headers? (Choose two.)

- A. sequence numbers
- B. congestion window
- C. MAC address
- D. window advertisements
- E. UDP datagram

**Answer:** A,D

**QUESTION:** 309

DRAG DROP

Click the Task button.

Two commands are used to configure an IPv6 6to4 Router. Place command segments in their places to complete these commands. Note: Not all text segments will be used.

The following two commands are used to configure an IPv6 6to4 Router.

Place the command segments in their places to complete the commands.

Note: Not all command segments will be used.

**Commands to configure IPv6 6to4 Router :**

ifconfig ip.6to4tun0 inet6 Place here

ifconfig Place here inet6 tsr Place here Place here /64 up

**Command segments**

192.168.102.42

ffe80:d0c1:1e11:fff::1

ip.6to4tun0

fec0:d0c1:1e11:fff::1

2002:d0c1:1e11:fff::1

plumb

ndpd

ip.6to4tun2

**Answer:**

The following two commands are used to configure an IPv6 6to4 Router.

Place the command segments in their places to complete the commands.

Note: Not all command segments will be used.

**Commands to configure IPv6 6to4 Router :**

ifconfig ip.6to4tun0 inet6 2002:d0c1:1e11:fff::1

ifconfig ip.6to4tun2 inet6 tsr ndpd 192.168.102.42 /64 up

**Command segments**

192.168.102.42

ffe80:d0c1:1e11:fff::1

ip.6to4tun0

fec0:d0c1:1e11:fff::1

2002:d0c1:1e11:fff::1

plumb

ndpd

ip.6to4tun2

**QUESTION:** 310

A system administrator is trying to boot a system from a network boot server. The system fails to boot and displays the following error: Timeout waiting for ARP/RARP packet Which command indicates whether or not the RARP packet arrived at the server and the server replied?

A. arp -a

- B. inetadm -d
- C. in.rarpd -da
- D. rarp -debug

**Answer:** C

**QUESTION:** 311

Click the Exhibit button.

The output from a netstat -r command is shown in the exhibit. In this output, the destination 192.168.100.0 is shown as an IP address. Which file should you modify to assign a name to this network so that this name is shown in the netstat -r output?

```
$ netstat -r

Routing Table: IPv4
  Destination          Gateway
  Flags Ref    Use   Interface
-----
192.160.100.0         router2          UG
1      0
localnet              myhost          U
1    5978 hme0
224.0.0.0             myhost          U
1      0 hme0
default              router1         UG
1      6 hme0
localhost            localhost       UH
4    66518 lo0
```

- A. /etc/inet/networks.conf
- B. /etc/default/networks.conf
- C. /etc/networks.conf
- D. /etc/inet/hosts
- E. /etc/inet/networks

**Answer:** E

**QUESTION:** 312

While configuring Solaris IP Filter on a system, you want to block all ICMP Redirect packets. /usr/include/netinet/ip\_icmp.h contains the following entry : #define ICMP\_REDIRECT 5 /\* shorter route, codes:/ Which rule should you add to your Solaris IP Filter configuration to block all such packets?

- A. block in quick proto icmp-type 5 from any to 0/32
- B. block in quick proto ip 5 from any to 0/32
- C. block in quick proto icmp from any to 0/32 icmp-type 5
- D. block in quick proto ip icmp-type 5 from any to 0/32
- E. block in quick proto 5 from any to 0/32

**Answer:** C

**QUESTION:** 313

DRAG DROP

Click the Task button.

Place each network component on the layer at which it operates.

Place each network component on the layer at which it operates.

Layers	Network Components
Application layer	Switch
Internet layer	Router
Network Interface layer	Intrusion Detection System
Hardware layer	Hub

**Answer:**

Place each network component on the layer at which it operates.

Layers	Network Components
Intrusion Detection System	Switch
Router	Router
Switch	Intrusion Detection System
Hub	Hub

**QUESTION:** 314

A Solaris 10 OS administrator needs to configure a host to operate as an NTP server. Which two must be performed on the host? (Choose two.)

- A. execute `/usr/sbin/ntp.server start`
- B. execute `snoop -d hme0 | grep NTP`
- C. execute `svcadm enable svc:/network/ntp`
- D. populate a `/etc/inet/ntp.conf` file
- E. edit the `/etc/inet/ntp.server` file

**Answer:** C,D

**QUESTION:** 315

DRAG DROP

Click the Task button.

Place each LAN component next to its description.

Place each LAN component next to its description.

LAN Components	Descriptions
Place here	connects networks that use different protocol suites
Place here	amplifies signals to extend the distance of transmission
Place here	connects network segments and filters/forwards packets
Place here	broadcasts all packets out all connected ports

**LAN components to be moved:**

bridge gateway hub repeater

Done

**Answer:**

Place each LAN component next to its description.

LAN Components	Descriptions
gateway	connects networks that use different protocol suites
repeater	amplifies signals to extend the distance of transmission
bridge	connects network segments and filters/forwards packets
hub	broadcasts all packets out all connected ports

**LAN components to be moved:**

bridge gateway hub repeater

Done

**QUESTION:** 316

Click the Exhibit button.

Which command yields the output shown in the exhibit?

Using the /dev/hme device (promiscuous mode)

```
sys12 -> sys11      ETHER Type=0800 (IP), size
= 98 bytes
sys12 -> sys11      IP D=192.168.1.1
S=192.168.1.2 LEN=84, ID=48009, TOS=0x0,
TTL=255
sys12 -> sys11      ICMP Echo Request (ID: 345
Sequence number: 0)

sys11 -> sys12      ETHER Type=0800 (IP), size
= 98 bytes
sys11 -> sys12      IP D=192.168.1.2
S=192.168.1.1 LEN=84, ID=45375, TOS=0x0,
TTL=255
sys11 -> sys12      ICMP Echo Reply (ID: 345
Sequence number: 0)
```

- A. snoop -d hme0 192.168.1.2
- B. snoop -d hme0 -V 192.168.1.2
- C. snoop -d hme0 -o /tmp/192.168.1.2
- D. snoop -v -d qfe0 broadcast
- E. snoop icmp

**Answer:** B

**QUESTION:** 317

You wish to add a static route to the routing table on your system. You add the following line to the /etc/defaultrouter file: net 129.159.158.0 gateway gw-157-158 metric 1 When the system is rebooted, you observe that the in.routed daemon has not started. The svcs -x command shows no problems. The netstat -r command does not show the static route in the routing table. What is the cause of this problem?

- A. The entry should have been placed in the /etc/gateways file.
- B. The entry should have contained the static keyword.
- C. The entry does not contain a netmask specification.
- D. The entry should use the IP address of the gateway, not its name.

**Answer:** A



Download Full Version From <https://www.certkillers.net>



**DON'T KNOW**  
OR NO PREFERENCE

*Pass your exam at First Attempt....Guaranteed!*