



Cisco

600-511

Designing with Cisco Network Programmability for ACI

QUESTION: 55

Which two options are components of a device package? (Choose two.)

- A. device configuration
- B. device specification
- C. device prototype
- D. device script
- E. device mapping

Answer: B, D

QUESTION: 56

Which two options are two intended uses of Layer 3-External in the ACI fabric? (Choose two.)

- A. to provide connectivity to external networks
- B. to advertise a default gateway into the ACI fabric
- C. to define the default gateway for the devices connected to the ACI fabric
- D. to advertise IP and MAC information outside of the ACI fabric
- E. to apply policy to endpoints not contained in an EPG

Answer: A, B

QUESTION: 57

What is the purpose of the mgmt tenant?

- A. used for in-band Cisco APIC to switch node communication, routable outside the fabric
- B. used for in-band and out-of-band Cisco APIC to switch node communication, nonroutable outside the fabric
- C. used for out-of-band Cisco APIC to switch node communication, nonroutable outside the fabric
- D. used for out-of-band Cisco APIC to switch node communication, routable outside the fabric

Answer: B

QUESTION: 58

Which network devices should be connected to the spine?

- A. Cisco APIC controllers
- B. leaf devices
- C. leaf and spine devices
- D. centralized security and load-balancing services for the fabric

Answer: B

QUESTION: 59

Which two types of data formats are supported by the RESTful APIs? (Choose two.)

- A. XML
- B. JSON
- C. SNMP
- D. HTTP
- E. CSV

Answer: A, B

QUESTION: 60

Where should network services be placed in an ACI fabric?

- A. spine
- B. leaf
- C. proxy VTEP
- D. Cisco APIC controller

Answer: B

Download Full Version From <https://www.certkillers.net>



DON'T KNOW
OR NO PREFERENCE

Pass your exam at First Attempt....Guaranteed!