



Cisco

642-964

*Cisco Data Center Networking Infrastructure Solutions
Support*

Answer: D

QUESTION: 51

What must be configured on the FWSM to forward traffic to a filtering server?

- A. the filtering server as an authentication provider (aaa-server)
- B. all web traffic so that it is directed only to the filtering server (access-list)
- C. all HTTP requests so that they are redirected to the filtering server (fixup protocol)
- D. all HTTP requests so that they are sent to the filtering server (url-server)

Answer: D

QUESTION: 52


How many IDSMs can be aggregated using a single EtherChannel in a highly available configuration?

- A. 2
- B. 4
- C. 8
- D. 32

Answer: C

QUESTION: 53

Refer to the exhibit.



Given this network design, which command would you use to configure traffic capture on the IDS?

- A. monitor session 1 source vlan 10

- B. monitor session 1 source vlan 20
- C. intrusion-detection module 5 data-port 1 access-vlan 10
- D. intrusion-detection module 5 data-port 1 access-vlan 20

Answer: A

QUESTION: 54

How do you enable the use of Cisco Adaptive Security Device Manager on an existing FWSM?

- A. Enable SNMP.
- B. Enable SSH.
- C. Enable the HTTPS server.
- D. Enable multiple contexts.

Answer: C

QUESTION: 55

What is the implication of executing the command failover interface-policy 2 on an FWSM?

- A. The configured failover interface policy will be applied to VLAN 2.
- B. The FWSM will fail over when more than one VLAN interface fails.
- C. The second configured failover interface policy will be applied to the FWSM.
- D. The FWSM will become active when it fails to receive two consecutive heartbeats from the paired FWSM.

Answer: B

QUESTION: 56

Which three values are user-configurable for risk ratings on the IDSM? (Choose three.)


- A. Target Value Rating
- B. Signature Age Rating
- C. Alert Reliability Rating
- D. Attack Severity Rating

- E. Signature Fidelity Rating
- F. Attack Probability Rating

Answer: A, D, E

QUESTION: 57

Refer to the exhibit.



Given this network design, which command would you use to configure traffic capture on the IDSM?

- A. monitor session 1 source vlan 10
- B. monitor session 1 source vlan 20
- C. intrusion-detection module 5 data-port 1 access-vlan 30
- D. intrusion-detection module 5 data-port 1 access-vlan 20

Answer: D

QUESTION: 58

What information is displayed when you execute this command on the IDSM?
show settings

- A. the management IP address
- B. the IDSM interface configuration
- C. the VLANs that are configured for traffic capture
- D. the VLANs that are configured for management access

Answer: A

QUESTION: 59

A POP3 and an SMTP server must be visible at the same address through an FWSM. Which type of NAT is required?

- A. dynamic NAT
- B. identity NAT
- C. policy dynamic NAT
- D. static NAT

Answer: D

QUESTION: 60

How many capture files can be stored on an IDSM?

- A. 1
- B. 4
- C. 8
- D. 32

Answer: A

Download Full Version From <https://www.certkillers.net>



DON'T KNOW
OR NO PREFERENCE

Pass your exam at First Attempt....Guaranteed!