

IBM

C2090-611

DB2 10.1 DBA for Linux, UNIX, and Windows

QUESTION: 110

Which statement about triggers is FALSE?

- A. A statement-level trigger fires only once for each SQL statement.
- B. A trigger's code block can be executed either before or after a triggeringevent.
- C. A row-level trigger fires once for each row that is affected by a triggering event.
- D. A table-level trigger fires once for each table that is affected by a triggering event.

Answer: D

QUESTION: 111

Which registry variable should be used to specify that 20 percent of each index page is to be left as as free space when building any index in any database?

- A. DB2_INDEX_DEFAULT
- B. DB2_EXTENDED_OPTIMIZATION
- C. DB2 INDEX PCTFREE DEFAULT
- D. DB2_ENABLE_AUTOCONFIG_DEFAULT

Answer: C

QUESTION: 112

A table named CUSTOMER and an index named CUST_IDX were created as follows:

```
CREATE TABLE customer
(id SMALLINT,
name VARCHAR(40),
phone VARCHAR(15),
address VARCHAR (100));
```

CREATE INDEX cust_idx ON customer (id, name);

If the following query is analyzed using Visual Explain:

SELECT id, name FROM customer;

Which operation would you expect to see in the access plan diagram produced?

- A. NLJOIN
- B. HSJOIN
- C. IXSCAN
- D. TBSCAN

Answer: C

QUESTION: 113

Which command will enableautomatic reorg on a database?

- A. UPDATE DB CFG USING AUTO_REORG ON
- B. UPDATE DB CFG USING AUTO_MAINT ON AUTO_REORG ON
- C. UPDATE DB CFG USING AUTO_TBL_MAINT ON AUTO_REORG ON
- D. UPDATE DB CFG USING AUTO_MAINT ON AUTO_TBL_MAINT ON AUTO_REORG ON

Answer: D

QUESTION: 114

How can you obtain information about any changes that have been made by the Self-Tuning Memory Manager (STMM)?

- A. By using the change history event monitor.
- B. By using the DB2 problem determination tool.
- C. By examining the contents of the system catalog.
- D. By examining the DB2 administration notification log file.

Answer: A

QUESTION: 115

Which statement about DB2 aggregate registry variables is true?

- A. An aggregate registry variable that is explicitly set by an application cannotbe overwritten.
- B. An aggregate registry variable overrides any corresponding explicitly set registry variable.
- C. A registry variable that is explicitly set by an application can only be overwritten by aggregate registry variable.
- D. A registry variable that is implicitly configured through an aggregate registry variable may also be explicitly defined.

Answer: D

QUESTION: 116

What must a user possess if they want to run a DB2 Command Line Processor (CLP) script against a database using the JobManager in IBM Data Studio?

- A. Permission to log in to the database client using telnet.
- B. Permission to log in to the database server using telnet.
- C. Permission to log in to the database client using secure shell (SSH).
- D. Permission to log in to the database server using secure shell (SSH).

Answer: D

OUESTION: 117

Which tool should be used to collect data during a potential hang without stopping the database manager?

- A. db2ls
- B. db2dart
- C. db2fodc
- D. db2cklog

Answer: C

OUESTION: 118

Which registry variable is used to enable transparent Lightweight Directory Access

Protocol (LDAP)?

A. DB2LDAP

B. DB2AUTH

C. CLNT_PW_PLUGIN

D. SRVCON_PW_PLUGIN

Answer: B

Download Full Version From https://www.certkillers.net

















