



Dell EMC

DES-4122 Exam

Specialist - Implementation Engineer, PowerEdge

Thank you for Downloading DES-4122 exam PDF Demo

You can buy Latest DES-4122 Full Version Download

<https://www.certkillers.net/Exam/DES-4122>

<https://www.certkillers.net>

Version: 5.0

Topic 1, Part 1, Misc. Questions

Question: 1

What is a requirement to operate GPUs in a Dell EMC PowerEdge R740 server?

- A. All GPU cards must be installed at the same time
- B. All GPU cards must be of the same type but can be a different model
- C. All GPU cards must be of the same type and model
- D. All GPU cards must be installed on the same riser card.

Answer: C

Explanation:

Question: 2

What is used by the Lifecycle Controller to directly back up the server profile on a 14G Dell EMC PowerEdge server?

- A. Network share
- B. vFlash SD card
- C. USB Flash drive
- D. IDSDM SD card

Answer: A

Explanation:

Question: 3

Where is the data stored to allow Easy Restore to successfully complete a system board replacement?

- A. NAND Flash module on the disk drive mid plane
- B. IDSDM SD card
- C. vFlash SD card

D. Serial Flash storage in the server's front panel

Answer: C

Explanation:

Question: 4

When does a customer require the Service Tag of the Dell EMC PowerEdge server?

- A. First time logging in to iDRAC
- B. First time accessing the BIOS
- C. Activating the OS
- D. Obtaining warranty information

Answer: B

Explanation:

Question: 5

DRAG DROP

What is the correct order of steps taken during the BIOS/UEFI Recovery process?

System boots to primary ROM	Step 1
iDRAC extracts the recovery BIOS image from a DUP saved in the control panel from the factory	Step 2
System disables the recovery ROM	Step 3
Connect to CLI of the affected server's iDRAC and run the racadm recover BIOS.Setup.1-1 command	Step 4
System initiates the recovery ROM and launches a BIOS update job	Step 5

Answer:

Explanation:

System boots to primary ROM	System boots to primary ROM
iDRAC extracts the recovery BIOS image from a DUP saved in the control panel from the factory	iDRAC extracts the recovery BIOS image from a DUP saved in the control panel from the factory
System disables the recovery ROM	Connect to CLI of the affected server's iDRAC and run the racadm recover BIOS Setup 1-1 command
Connect to CLI of the affected server's iDRAC and run the racadm recover BIOS Setup 1-1 command	System disables the recovery ROM
System initiates the recovery ROM and launches a BIOS update job	System initiates the recovery ROM and launches a BIOS update job

Thank You for trying DES-4122 PDF Demo

To Buy New DES-4122 Full Version Download visit link below

<https://www.certkillers.net/Exam/DES-4122>

Start Your DES-4122 Preparation

[Limited Time Offer] Use Coupon “CKNET” for Further discount on your purchase. Test your DES-4122 preparation with actual exam questions.

<https://www.certkillers.net>