

## **EMC**

#### E20-307 Exam

# Prepare for EMC VMAX3 Solutions Specialist Exam for Implementation Engineers

Thank you for Downloading E20-307 exam PDF Demo

You can Buy Latest E20-307 Full Version Download

https://www.certkillers.net/Exam/E20-307

	Version: 8.0
Question: 1	
Please check the option that bes	t describes your relationship with Dell EMC:
A. Dell EMC Employee B. Dell EMC Customer/Partner C. Other	
	Answer: C
Question: 2	
CORRECT TEXT Please enter your Powerlink Use know your Powerlink Username Powerlink Username:	ername below. If you do not have a Powerlink Username or do not enter none.
	Answer: Varies
Question: 3	
What are pre-configured in VMA	X3 and VMAX All Flash arrays?
A. SRDF devices B. Gatekeeper devices C. Thin devices D. Data devices	
	Answer: C
Question: 4	
	of source volumes has been linked to target volumes. The target cation testing. What should be done prior to a relink operation?
<ul><li>B. Continue accessing the source</li><li>C. Stop accessing the source and</li></ul>	
	Answer: A

<b>Ouestion</b>	٠. 5
Questioi	ı. o

A VMAX3 parent Storage Group (SG) contains two child SGs: SG1 and SG2. What is a valid bandwidth limit setting for this cascaded Storage Group?

- A. Parent SG 400; SG1 500; SG 200
- B. Parent SG 400; SG1 500; SG NOLIMIT
- C. Parent SG 500; SG1 500; SG 400
- D. Parent SG 500; SG1 NOLIMIT; SG 1000

Answer: C

#### Question: 6

At which levels are FAST performance metrics collected in a VMAX3 array?

- A. Disk Group, Storage Group, and thin device sub-LUN
- B. Data Pool, Storage Resource Pool, and Storage Group
- C. Disk Group, Data Pool, and thin device sub-LUN
- D. Disk, Data Pool, and Storage Resource Pool

Answer: A

#### Question: 7

DRAG DROP

What is the correct sequence of actions performed by a VMAX3 when the SRDF failback command is executed?

Read/Write enable the R1 devices	STEP 1
Merge the device track tables	STEP 2
Suspend the RDF links	STEP 3
Write disable the R2 devices	STEP 4
Resume the RDF links	STEP 5
	Answer:
Read/Write enable the R1 devices	Write disable the R2 devices
Merge the device track tables	Suspend the RDF links
Suspend the RDF links	Merge the device track tables
Write disable the R2 devices	Resume the RDF links

#### **Question: 8**

Which Solutions Enabler environment variable can be set to stop the user from getting asked for confirmation during command execution?

- A. symcli\_noprompt
- B. symcli\_command\_scope
- C. symcli\_mode
- D. symcli\_output\_mode

Answer: A

Explanation:

Reference:

https://www.emc.com/collateral/TechnicalDocument/docu46983.pdf (page 243)

### Thank You for trying E20-307 PDF Demo

To Buy Latest E20-307 Full Version Download visit link below

https://www.certkillers.net/Exam/E20-307

# Start Your E20-307 Preparation

[Limited Time Offer] Use Coupon "CKNET" for Further discount on your purchase. Test your E20-307 preparation with actual exam questions.