



Huawei

H19-368_V1.0

HCS-Pre-sales-Transmission & Access V1.0

QUESTION & ANSWERS

Product Questions: 301

Version: 4.0

Question: 1

Enhanced MSTP evolved from MSTP, focusing on the technical aspects of packet service bearer Evolution is not a change in equipment.

- A. TRUE
- B. FALSE

Answer: A

Question: 2

Enhanced multi-service transport node (MSTP) equipment technical requirements, in line with standard YD/T 2486-2013 requirements

- A. TRUE
- B. FALSE

Answer: A

Question: 3

The enhanced MSTP solution not only supports the physical isolation of VC particles, but also supports ODUK particles Granule physical isolation

- A. TRUE
- B. FALSE

Answer: A

Question: 4

The enhanced MSTP solution does not support the 1588V2 synchronization mode.

- A. TRUE
- B. FALSE

Answer: B

Question: 5

SDH basic transmission module is STM-4

- A. TRUE
- B. FALSE

Answer: B

Question: 6

There are 32 time slots for 2M signals in SDH standard

- A. TRUE
- B. FALSE

Answer: A

Question: 7

The definition of OTN is Open transmission network.

- A. TRUE
- B. FALSE

Answer: B

Question: 8

OTU units can be used in docking with different FEC types, such as AFEC at the originating end, The receiving end uses FEC.

- A. TRUE
- B. FALSE

Answer: B

Question: 9

The maximum electrical crossover capacity of OSN 9800 U32E is 32T.

- A. TRUE
- B. FALSE

Answer: A

Question: 10

ODU0 frame rate is 1.25Gbits/s, ODU1 frame rate is 2.5Gbits/s, ODUflex frame rate is 40Gbits/s

- A. TRUE
- B. FALSE

Answer: B

Question: 11

OSN 1800 supports OTN ASON

- A. TRUE
- B. FALSE

Answer: A

Question: 12

WDM system, the noise is mainly introduced by EDFA amplifier

- A. TRUE
- B. FALSE

Answer: A

Question: 13

The name of MS-OTN is Multi-Service Optical Transport Network

- A. TRUE
- B. FALSE

Answer: A

Question: 14

Huawei WDM does not support OSNR detection at 100G wavelength