

Huawei

H19-368_V1.0

HCS-Pre-sales-Transmission & Access V1.0

QUESTION & ANSWERS

Product Questions: 301 Version: 4.0

Ougstion, 1
Question: 1
Enhanced MSTP evolved from MSTP, focusing on the technical aspects of packet service bearer Evolution is not a change in equipment.
A. TRUE B. FALSE
Answer: A
Question: 2
Enhanced multi-service transport node (MSTP) equipment technical requirements, in line with standard YD/T 2486-2013 requirements
A. TRUE B. FALSE
Answer: A
Question: 3
The enhanced MSTP solution not only supports the physical isolation of VC particles, but also supports ODUK particles Granule physical isolation
A. TRUE B. FALSE
Answer: A
Question: 4

The enhanced MSTP solution does not support the 1588V2 synchronization mode.

B. FALSE		
		Answer: B
Question: 5		
SDH basic transmission module	e is STM-4	
A. TRUE		
B. FALSE		
		Answer: B
Question: 6		
There are 32 time slots for 2M	signals in SDH standard	
A. TRUE B. FALSE		
		Answer: A
Question: 7		
The definition of OTN is Open t	ransmission network.	
A. TRUE B. FALSE		
		Answer: B
Question: 8		
OTU units can be used in docking The receiving end uses FEC.	ng with different FEC types, such as AFE	C at the originating end,
A. TRUE B. FALSE		
		Answer: B
Question: 9		

The maximum electrical crossover capacity of OSN 9800 U32E is 32T.

A. TRUE

	Answer: A
Question: 10	
ODU0 frame rate is 1.25Gbits/s, ODU1 frame rate is 2.5Gbits/s, ODUflex	x frame rate is 40Gbits
A. TRUE B. FALSE	
	Answer: B
Question: 11	
OSN 1800 supports OTN ASON	
A. TRUE B. FALSE	
	Answer: A
Question: 12	
WDM system, the noise is mainly introduced by EDFA amplifier	
A. TRUE B. FALSE	
	Answer: A
Question: 13	
The name of MS-OTN is Multi-Service Optical Transport Network	
A. TRUE B. FALSE	
	Answer: A

Huawei WDM does not support OSNR detection at 100G wavelength