



McAfee

MA0-101 Exam

McAfee Certified Product Specialist- NSP Exam

Thank you for Downloading MA0-101 exam PDF Demo

You can Buy Latest MA0-101 Full Version Download

<https://www.certkillers.net/Exam/MA0-101>

<https://www.certkillers.net>

Question: 1

Which port needs to be opened for Alert Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

Answer: B

Question: 2

Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method?

- A. Signature based
- B. Pattern matching
- C. Denial of Service
- D. Remediation

Answer: C

Question: 3

Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?

- A. sensor perf-debug 100
- B. sensor perf-debug on 100
- C. sensor perf-debug Interface all 100
- D. sensor perf-debug assert 100

Answer: A

Question: 4

What type of encryption is used for file transfers between the Sensor and the Manager?

- A. SSL with RC4
- B. SSL with MD5
- C. SSL with RC4 and MD5
- D. DES

Answer: D

Question: 5

When placed in Layer3 mode, a Sensor detects a Layer2 device based on which of the following?

- A. MAC address
- B. IP address
- C. DNS
- D. Subnet

Answer: B

Question: 6

What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?

- A. arp spoof status
- B. arp spoof enable
- C. arp dump
- D. arp flush

Answer: C

Question: 7

DoS detection is implemented in which of the following modes? (Choose two)

- A. Learning mode
- B. Configuration mode
- C. Threshold mode
- D. Bidirectional mode
- E. Inbound mode

Answer: A, C

Question: 8

Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?

- A. 8501
- B. 8502
- C. 8503
- D. 8555

Answer: C

Question: 9

Which port is correctly defined for the Alert Channel on the Network Security Manager?

- A. 8500
- B. 8501
- C. 8502
- D. 8504

Answer: C

Question: 10

In double VLAN tagging, a second VLAN tag that is inserted into the frame is referred to as which of the following?

- A. Customer Identification tag (CD)
- B. VLAN Identification tag (VID)
- C. Outer Identification tag (OID)
- D. Inner Identification tag (HD)

Answer: A

Thank You for trying MA0-101 PDF Demo

To Buy Latest MA0-101 Full Version Download visit link below

<https://www.certkillers.net/Exam/MA0-101>

Start Your MA0-101 Preparation

[Limited Time Offer] Use Coupon “CKNET” for Further 10% discount on your purchase. Test your MA0-101 preparation with actual exam questions.

<https://www.certkillers.net>